

SC- PTZ M5/M6-XPower

22 and 27 Times PTZ camera

Camera Highlights

- ◆ Support Multiple Protocols including Pelco D-type, Pelco P-type etc
- ◆ Offer 22 times and 27 times Optical Lens
- ◆ Use 1/4" Hi-Resolution Color CCD Camera
- ◆ Auto focus and Iris Lens
- ◆ Pan Speed is 0.5°/Sec to 50°/Sec Vari-speed
- ◆ Power input : AC24V (outdoor) ; DC12V (indoor)
- ◆ Support Auto Pan function
- ◆ Support Auto Preset tour function
- ◆ Communication uses RS485 data port
- ◆ ID address up to 256



**6" OUTDOOR
Vandal
Wall Mount**



**7" INDOOR
Ceiling Mount**

- Securtex XPOWER Speed Dome Camera offers 2 different solutions : 22 times (352x Digital Zoom) and 27 times Optical Zoom (270x Digital Zoom) Lens.
- XPOWER offers 1 Preset tour with 32 preset points, able to program the camera to follow a continuous memorized path-panning, tilting and zooming at any speed you expect and stopping at selected targets along the way.
- Able to choose Day&Night camera, this solution will automatically switch to Color or B/W images during Daytime and Nighttime, (during daytime, it will be in Color mode; and in nighttime, it will be in B/W mode), while you can also choose "Auto" or "Manual" mode per the request of environment conditions.
- XPOWER offers different power choices: DC12V(indoor), AC24V(outdoor), Such flexibility of power can meet easily the local safety request of different countries.
- XPOWER uses the most solid VANDAL DOME to prevent the strong heavy strike / destroy by intention in the outdoor conditions.
- XPOWER offers 100% Dust-proof and Water-proof function with IP66 standard. In particular our Dome Enclosure is using "total die-cast aluminum structure" material, it can out-perform the best protection when installed in "Outdoor environment".
- Outdoor XPOWER offers fan + heater which allow outdoor dome to be operated under a very wide range of temperature from +60°C to -30°C without safety concern.

Model Specifications

	SECURTEX XPOWER	
Image Device	1/4" Color CCD	
Picture Element	NTSC: 380,000. pixels PAL: 440,000. pixels	
Sync-sync	Internal / External	
Lens	22 times Optical Lens f=3.9mm to 85.8mm F=1.6 to 3.7	27 times Optical Lens f=3.25mm to 88mm F=1.5 to F3.6
Digital zoom	352 times Digital Zoom	270 times Digital Zoom
Focus system	Auto / Manual	Auto / Manual
Min. working	0.01M(wide)	0.01M(wide)
H-Resolution	480TV Lines	480TV Lines
Min illumination	1.0Lux / F1.6 Color	1Lux / F1.5 Color B/W Mode: 0.1Lux Night Mode IR CUT ON : 0Lux B/W Mode
S/N ratio	More than 48 dB	More than 48 dB
Auto White Balance	Auto / ATW	Auto / ATW
Pan movement	0° ~ 360° continuous endless	
Tilt movement	0° ~ 90°	
Pan speed	0.5°/SEC to 50°/SEC vari-speed	
Tilt speed	0.5°/SEC to 50°/SEC vari-speed	
Preset	32 preset	
Communication	RS485 interface	
ID address	1 ~ 256 address	
Power supply	DC12V / AC24V	
Outdoor	IP66	

XA-301 **Outdoor pendant mount** **QA-302** **Outdoor corner wall mount**
QA-305 **Outdoor Pole mount kit** **QA-306** **Outdoor Waterproof Box**
QA-307 **Outdoor Waterproof Box + AC220V to AC24V adapter**